

# Opto-sensor set



## Article

---

Item no.	Description
160264	<b>Opto-sensor set</b> consisting of transmitter with 10.5 m cable, receiver with 1 m cable, adapter sleeves 11/22 mm

## Scope of delivery

---

- F photoelectric sensor transmitter with 10,500 mm cable
- F photoelectric sensor receiver with 1,000 mm cable
- 2 F spacer sleeves 11/22 mm

## Use

---

### F spacer sleeve set 11/22 mm

- For opto-sensors with 11 mm diameter. For bottom door profiles with receptacle for 22 mm opto-sensors

## Technical data

---

### F-Transmitter

- Connection type: Conventional
- Interfaces: OSE
- Protection class: IP68

- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 75
- Temperature (min./max.)[°C]: -20/75
- Range [m]: 10
- Operating voltage [V]: 4-28 V-DC
- Diameter [mm]: 11
- Length [mm]: 37
- Cable length [m]: 10.5

## F-receiver

- Connection type: Conventional
- Interfaces: OSE
- Protection class: IP68
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 75
- Temperature (min./max.)[°C]: -20/75
- Range [m]: 10
- Operating voltage [V]: 4-28 V-DC
- Diameter [mm]: 11
- Length [mm]: 37
- Cable length [m]: 1

## F spacer sleeve set 11/22 mm

- Diameter inside [mm]: 11
- Outer diameter [mm]: 22
- Length [mm]: 30
- Weight [kg]: 0.01
- Packing width: 51
- Packing height: 25
- Packing depth/length: 59
- Packing weight: 0.021
- Freight forwarding articles: No
- GTIN: 4062435001553
- Customs tariff number: 40091100
- Country of origin 1000: Deutschland
- Garantie: -